GX-3016-_{TWIN}

Sources *Microphone console*



- Up to 2x16 zones
- Integrated 3-tone chime
- O Power supply over Bus
- **Easy and quick installation**
- Inconspicuous and multipurpose

The **GX-3016-TWIN** is a zone-selection paging microphone console: 2x16 zones. As it works on the same bus architecture as GX3016, it enables to control two CC3816 or CS2600 matrixes in parallel while keeping the advantage of bus distribution.

The **GX-3016-TWIN** is therefore easily integrated in a network of GX3016 and GXT4000.

Provided with an electret microphone, 2×16 programmable keys, 4 function keys and 1 chime, this console meets all your needs in Public Address.

Either put on a table or flush-mounted, this console can be used in several application types.

Features			Applications
Keyboard	2x16 key zone selection	4 function keys	Speech
Series connection	Bus	RS 485	
Power supply	24 VDC	Cons.: 120 mA max	Checkpoint
Dimensions		385 x 175 x 50 mm	Meeting point Information
Color	Shiny grey console	Matt grey base	Offices
Material		Metal	
Weight		1,3 Kg	

GX-3016-_{TWIN} **Sources** Microphone console **Top view** Electret microphone 1 Under voltage Light 2 3 Busy audio bus Light « Zone selection » keys + lights 4 « Function » keys + lights SOUYER **Bottom view** 0000 0000 OOOO 0000 0 Remote power supply connector 1 0 RJ 45 IN/ Out connectors for audio / command 2 bus linkage CAT5-type cable Matrix connection principle RJ45-RJ45 right 8 conductors 1 audio bus pair 1 RS485 pair 1 free pair 1 x 24Vdc power supply pair Central equipment Central equipment

Type CC3816

Type CC3816