







-  **Coverage up to 70 sq.m**
-  **AGC Automatic Gain Control**
-  **Small dimensions**
-  **Easy installation**

The **IL-070** is a magnetic loop amplifier for spaces of around 70 sq.m. Provided with Automatic Gain control (AGC), it guarantees constant maintenance of the sound level preselected through the various made adjustments. Four (4) buttons on front panel allow to easily select the source to be broadcasted among digital TOSlink/coaxial interface, the 2 Line (RCA) inputs and the 2 MIC (jack) inputs. Operating under 18Vac, the IL-070 can meet your embedded requirements in tourist buses. This item is delivered with 40m BIM cable, cable grips, a TOSlink cable, a connexion cord and a base for vertical positioning, which ensures easy and quick installation.



*Hearing aids with integrated telephone coil receive its signals (selector position on »T« or »MT«).*

### Features

<b>Inputs</b>	1 SP- DIF	2 LINE (RCA) 2 MIC (Jack)
<b>Output</b>	Headset Jack 3,5 mm	Induction Clamp terminals
<b>Induction</b>	4 A RMS	0,5-1,5 Ohm
<b>Power supply</b>	External block	100-240 VAC 12-24 VDC
<b>Dimensions</b>	L x l x P	180 x 42x 140 mm
<b>Colour</b>		Aluminium grey
<b>Material</b>	Front box	Metal – class 2 ABS plastic
<b>Weight</b>		905g

### Applications

**Public address.....**



 **Classrooms**

 **Counters**

 **Places of worship**

 **Museums**

 **Vehicles**

