Voice Alarm speaker Enclosure


EN 54 - 24 Certified




- High intelligibility
- **Sound quality**
- Ontemporary design
- Easy and quick installation

The **ML-260-EN5424** is an enclosure-type sound broadcaster, with 2 ways bass-reflex. This loudspeaker offers excellent sound properties for background music and spoken messages, which enables to get a high quality installation in places requiring high comfortable listening.

Its contemporary design enables integration in any type of environment. Its fixing device facilitates its orientation and ensures easy and quick installation.





-					
	e2	7 7	•	20	
IN			••		S

Loudspeaker	2 ways		
Powers	30W nominal	30 / 15 / 7,5 / 3,75 W	
Frequency band		60 Hz – 20 kHz	
Sensitivity	1W / 1m (5,5kHz) 30W / 1m (5,5kHz)	92 dB 107 dB	
EN54-24	Pink noise 1W/4m Max 30W/4m	73 dB 87,9 dB	
-6dB openings	500Hz 4kHz	360° 84°	
Dimensions		245 x 180 x 165 mm	
Color		Black / White	
Material		ABS	
Weight		2,6Kg	

Applications

Voice Alarm system.....



Music.....



Speech



Bar rooms

Shops

Restaurants

Waiting rooms

Sports rooms



NB: As per the norm, the use of VA—casing is necessary