





BAT-XXXAH

Voice alarm system Batteries

Conforme **EN 54 - 4**



-  **Watertight**
-  **Gelled lead**
-  **ABS**
-  **100% recyclable**

BOUYER selected the best lead batteries on the market.

They have been designed to optimize system performances and protect from electrical overloads.

Materials used ensure optimal safety :

- seals prevent acid leakage at very high temperature,
- safety valve enables excess gas to escape in case of overload,
- firewall prevents any spark to get into the battery,
- body out of ABS ensures unequaled mechanical resistance.

Features

Grid	Lead – calcium Tin alloy
Separator	Electrolytes absorbed High microporosity
Terminals	Make installation easy
Seals	Prevent acid leakage
Valves	Allow gas escape
Firewall	Prevent from sparks
Body	ABS

Dimensions

References	Dimensions L x P x H	Weight kg
BAT-24AH	166 x 175 x 125	9
BAT-27AH	166 x 175 x 117	9
BAT-38AH	197 x 165 x 170	14,2
BAT-42AH	197 x 165 x 170	13,8
BAT-70AH	272 x 166 x 191	23,2
BAT-100AH	329 x 172 x 214	32,5
BAT-120AH	407 x 173 x 220	38
BAT-150AH	483 x 170 x 220	46,2

