BIM-60M2

Induction loop system Small surfaces kit

Key points

(Small surfaces kit, 60m² max.

(Easy and invisible installation

(Surface microphone supplied

(Compliant EN60118-4





Loop cable supplied Length = 35m



Mains power supply

Surface microphone Discreet, ideal counter

> Ultra-compact amplifier **Credit card size**

More details

This induction loop kit enables to equip small areas up to 60 square meters. It also enables to meet equal opportunity standards and to respect IEC-60118-4 standard requirements. Its induction loop is directly integrated in an "hearingimpaired" panel for convenient installation. It is designed to offer access to people with a hearing device including "T" switch.

The amplifier is made to be discreetly fixed under a desk or counter. Its is equipped with two inputs, parameters and LED indicating power + loop status. It also integrates an audio processor to avoid not desired and important sound level variations.

FEATURES	
Power supply	12V DC / 1,5A (mains)
Inputs	2 (1 microphone / line level + 1 line level) Euroblock connectors
Output	RMS current = 2 A @ 1 kHz, Peak current = 3,5 A
Dimensions (W x l x H)	92 x 52 x 18 mm
Weight	0,85 kg
Color	Black
Accessories	Mains power supply / Surface microphone / 35m loop cable / 3 stickers "Hearing-impaired areas" / AUX cable

