## **CONF-PD-DSP-V**

## Conference Wired delegate console

## **Key points**

Wired delegate console

Built-in speaker

Sensitive keys + OLED screen

Choice of listening language + voting function

Microphone cell (cardioid) Ideal for conference system

Built-in speaker
Live broadcast of exchanges



Embedded OLED screen

Speaking time / Language... displayed

Jack 3.5mm input **Headphones connection** 

Backlit sensitive keys

Speaking + voting

## **More details**

The CONF-PD-DSP-V console uses a cardioid microphone cell (captures sounds coming from the front) suitable for a conference system.

It allows the delegate to freely speak or with chairman validation depending on the mode chose on the central unit.

It is also possible to choose the listening language (a headset is then recommended) and to take part in votes.

Its OLED screen also displays the speaking time, the listening language selected, date & hour... It easily connects to the system thanks to its RJ45 input and can be chained with another console thanks to its second RJ45 output port.

FEATURES	
Directivity	Cardioid
Bandwidth	20 Hz – 20kHz
Gooseneck	41 cm
Connectors	2 x RJ45 (IN / OUT for console chain) 3.5mm stereo headphone jack 3.5mm microphone jack
Power	Supplied by CONF-UC-DSP central unit
Base dimension	18,5 x 5 x 13 cm (L x h x l)
Color	Black
Material	ABS
Weight	1,1 kg (with gooseneck microphone)
Others	2m RJ45 cable supplied

